

## Air water flow conditions on spillway channels downstream of Piano key weirs

**Auteur :** Dalem, Juliette

**Promoteur(s) :** Erpicum, Sébastien

**Faculté :** Faculté des Sciences appliquées

**Diplôme :** Master en ingénieur civil des constructions, à finalité spécialisée en "civil engineering"

**Année académique :** 2022-2023

**URI/URL :** <http://hdl.handle.net/2268.2/17726>

---

### Avertissement à l'attention des usagers :

Tous les documents placés en accès ouvert sur le site le site MatheO sont protégés par le droit d'auteur. Conformément aux principes énoncés par la "Budapest Open Access Initiative"(BOAI, 2002), l'utilisateur du site peut lire, télécharger, copier, transmettre, imprimer, chercher ou faire un lien vers le texte intégral de ces documents, les disséquer pour les indexer, s'en servir de données pour un logiciel, ou s'en servir à toute autre fin légale (ou prévue par la réglementation relative au droit d'auteur). Toute utilisation du document à des fins commerciales est strictement interdite.

Par ailleurs, l'utilisateur s'engage à respecter les droits moraux de l'auteur, principalement le droit à l'intégrité de l'œuvre et le droit de paternité et ce dans toute utilisation que l'utilisateur entreprend. Ainsi, à titre d'exemple, lorsqu'il reproduira un document par extrait ou dans son intégralité, l'utilisateur citera de manière complète les sources telles que mentionnées ci-dessus. Toute utilisation non explicitement autorisée ci-avant (telle que par exemple, la modification du document ou son résumé) nécessite l'autorisation préalable et expresse des auteurs ou de leurs ayants droit.

---

# Air water flow conditions on spillway channels downstream of Piano key weirs

**Juliette Dalem**

Supervisor: S.Erpicum  
Master in Civil Engineering, University of Liège  
Academic year 2022-2023

## **Abstract**

Piano Key Weirs (PKWs) are an improvement of labyrinth key weirs. This type of weir can be placed on the dams needing to be restored, which is an advantage given the number of ageing dams. PKWs are used as the crest of spillways in order to manage water discharge, mitigate flood risks, and maintain the structural integrity of the dams. However, few studies have been carried out on flow properties downstream of this type of weir.

The main aim of this research work is to compare different flow properties as the clear water depths, the velocities, the air concentration profiles or the dissipated energy for different spillway types for a steep slope. Three weirs are tested: a Creager weir and two PKWs with different geometries. For each weir, a smooth and a stepped spillway are placed, making a total of six configurations tested. The results are obtained with a double-tips conductivity probe.

Different conclusions were drawn from the results obtained in this work. Firstly, more air is entrained in the flow for stepped spillways than for smooth spillways. Moreover, in the case of smooth spillway, the air entrainment is more important for PKWs while, for the stepped spillways, the air entrainment can be considered to be the same for the different weirs. Then, a non-uniformity of heads across the width of the channel appears downstream the PKWs. The head variation is greater for smooth spillways than for stepped spillways. Finally, the stepped spillways dissipate more energy than smooth spillways. Moreover, the type of weir seems to have a small influence on the dissipated energy. Even if the difference is not very important, the dissipated energy is slightly greater in the case of a Creager weir than PKWs.